

Wall mounted receptacle

Part no. 5638A




- screw terminals
- **X-CONTACT**
- switched
- mechanical DUO-interlock
- DIN rail
- receptacles can be padlocked

Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 32 A |
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 67 |
| Enclosure material | Plastic |
| Weight | 2119 g |
| Declaration of Conformity | EAC, CQC |

Drawing



| Drawing | Amp. | 16 | | | 32 | | 63 | |
|---|------|-------|-------|-------|-------|-------|------|------|
| | | Poles | | | 4 | 5 | 4 | 5 |
| 1 MB 181/620 | | | | | | | | |
| Dim. in mm | | | | | | | | |
| a | | 364 | 364 | 364 | 364 | 364 | 460 | 460 |
| b | | 134 | 134 | 134 | 134 | 134 | 180 | 180 |
| c | | 160 | 162 | 163 | 168 | 168 | 202 | 202 |
| d | | 347 | 347 | 347 | 347 | 347 | 440 | 440 |
| e | | 117 | 117 | 117 | 117 | 117 | 160 | 160 |
| f | | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | 8.1 | 8.1 |
| g | | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| h | | 391 | 395 | 398 | 408 | 411 | 505 | 505 |
| M | | 32/40 | 32/40 | 32/40 | 32/40 | 32/40 | 40 | 40 |
| M* | | 2x32 | 2x32 | 2x32 | 2x32 | 2x32 | 2x40 | 2x40 |
| Max. cable diam. (mm) | | 27 | 27 | 27 | 27 | 27 | 27 | 27 |
| Terminal for cond. cross section (mm ²) min.-max. | | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 6 | 6 |
| | | -4 | -4 | -4 | -10 | -10 | -25 | -25 |